10-14-1964 set C/M over 1/2"x30" rod set M&L. (1)
This 1/4 Cor. is M&L by Kerr — Note: Perry's Cor. Set from BT's 2641.6
1/4 Corner 16-21 New Haven 108-15
#851604
12-1871 Perry by Hunter P189 N6 206 & 21 Donahue, Brown.
Corner gone, reset from witness trees.
-16 south set stake M&L 19.91
-16 west " " " 20.02 1/2. - also 15.02 5.01 west of 1/4 Cor

9-1964 J Kerr B89 P63. & 16 Swentlund.
run section line set C/M. over 1/2"x30" rod after extensive digging along old fence balk in open pasture.
total meas 5283.2

-over-

- set steel fence post west 1.0
- line of N-S fence running south west 6.0.
- fence running east & west south 19.0
- old fence balk running east & west plain
  can't figure why fence is 19' south although land is
  common owned in all 4 ways.
- center road running northwestly 3670.9.± - East of S.W. 16
- run 1/4 line north see center 16.

Tom Ferguson - Jan. 1974 - found 3/4" to 1" dia. iron rod in 4 Co. Rund
also fd - pipe about 1.3' N. of rod & pipe is on Sec. line according
To T. Ferguson's work and possibly set by T. Taylor's Crew

¼ Cor. 16-21

New Haven Twp.

(2)

#851604

Gov. Notes- Cushing, Dept. Sur. 6-12-1854
West on true line between 16 and 21.
39.99 Set quarter section post.
Br. Oak 8 in. N3E 52 lks.
79.98 Section corner.

9-16-81 1/16 West: Started digging with backhoe over a point on line from SW 16 to SE 16 and at Hunter's measure from SW 16. Dug 7' deep to clay. There was no black dirt left. Had driven on clay! Did not dig further.