/ 8/7189 C.H.D. SET 5/8" BRASS PLUG

#851806 (1)

1/4 corner west 1/4 18 New Haven. 10 8-15
3-1892. Thos Fraser. P471 no 452 & 18. Kennedy, Kane & others.
found 2 boulders with stake between set many years
before by man that owned land to the northwest
& horse shoe claimed could be found below.
- meas east 39.10 1/2 (2580.68'

---

1-1896 H Fraser P589 no 535 west line & 18.
found corner P471.
- meas south. 39.59 1/2 (2613.3 which is 1/4 the
distance W 1/4 18 to W 1/4 30.

Oct. 1853 Gov't Notes- Ball, Dept. Sur.
35.40 Br. Oak 8 in,
40.00 Set quarter section post.
Br. Oak 8 in. South 460 ~~lks~~ lks.
Br. Oak 10 in. S78E 131 lks.

5-14-1980 (1980 Roman BK) W 1/4 Cor 18: Dug with backhoe. Found large limestone 9' deep and beneath old clay culvert which we broke and removed. The stone is 1.9 West and .75 North of the traverse nail here. We had dug here on 5-9-1980 farther East. We dug a huge hole in the East lane of the road & 10' deep to clay, reaching 3' North & 15' South of the traverse nail. After finding some of Will Frasier iron to the South, his line indicated that this corner would be farther West so we dug again today. We could not go down into the hole to get a close look at the stone since there was a chance the previous diggings would collapse into our new hole.

1/4 Corner West 1/4 Cor. 18 New Haven 108-15 (2)
#851806

5-28-1980 (1980 Lemon Bk., Page 44-45) W1/4 18: Set a 1/2" x 18" rod on line from the W 1/4 Cr 30 projected over W. 18-19 and at 1/3 the distance from W 1/4 Cr 30 to W. 18-19 North of W. 18-19 as per W.F. Survey No 535. The corner came in line with the fence West and 4.7 West of present ℄. The corner is 1.5 West and .57 South of the t.n. (The calc. location was .48 South and 1.31 West of the t.n.) We decided to set the corner by this method since W.F.'s work from W1/4 30 to W 18-19 was so good and we were unable to get down to examine the corner found here 5-14-80

RP's: Punched cross in top East end 48" C.M.P. NE 64.47
Punched cross in top West end 48" C.M.P. NW 60.75

7-16-85, W 1/4 18: This corner may be destroyed by road construction. Took transit ties.

Set 3/4" re-rod (down 12") ± 1' South of fence West

Set 5/8" re-rod under fence West 234.49 west of 3/4" re-rod.

π @ 3/4" re-rod. Meas east to W 1/4 Cn 18 (1/2" re-rod) = 108.16

x Rt 5/8" re-rod to W 1/4 18 = 179° 57' 42"

8/7/89 C.H.D. SET 5/8" BRASS PLUG IN ℄ C.R. #5, CORNER INLINE WITH FENCE WEST