#851904 (1)

/ Corner lost 10-71)

1/4 Corner 19-30 New Haven 108-15

11-6-1874 Hunter P264 No 262 S 30 R. Cornforth & others after careful search from stump of SW BT found remains of old stake.

- set new stake and took 2 witness trees.
  10" br oak S 65½ E 57 lks - 37.62'
  12" br oak S 7° W 69 lks 45.54
- 16 east set stake M & L 19.96 (1317.36'
- Meas south to center 30 (a stone 4 x 5 x 12 found 10-20-71. and stake) set at true intersc lines 39.71 (2620.86

5-1910 Ch Larson P124 B S 30 Sam Cloener.

this survey confusing as to way drawn and described over)

accepting top of drawing as east (not north) corners and measurements make good sense otherwise not.
1/4 19-30 not used but evidently aerial of E-W 1/16 & N 1/2 30
run and point set 38.27 (2525.82 east of iron set
as 1/16 M&L 19.82 (1308.12' W Frazer got 1306.65'
between same corners — govt means west 1/2. 30 N 3850
Hunters E 1/2 2634.72 so 38.27 could be acceptable as mean. S 3819
P. 124 B corner as "4" written as 1/4 cor I could not be certain
30 as north 1/2 mile "3" written as Sec corner 1/4 Corner limestone.
with 1/16 north 19.89 1312.74 an iron stake.

So 1/4 19-30 a last corner - walked to corner area and found entire area dozed with power machinery. Trees in massive pile. S 1/4 searched for 10' deg in road (also last) centerstone in good shape found. 10-20-71.

#851904

(2)

¼ Cor. 19-30 New Haven Twp.

6-12-1854 Gov't Notes- Cushing, Dept. Sur.
East on true line between 19 and 30.
38.50 Set quarter section post.
Aspen 6 in. N31E 33 lks.
Aspen 5 in. ?66W 11 lks.
78.50 SECTION corner