/ 12-1-69 set C/M over iron in lime hole, rig stone on S side section corner. 20-21-28-29 New Haven 108-15 (1)
#852105

6-1910 Ch Larson P126 B NE cor S20 Hooke, Soldner found stake drilled hole 2½' deep, filled with lime, set stone on top:

- south set stake at 9.97 chs from 9.97 to 1/16 corner set up same as above section corner. found 1/16 stake.
- west set oak stake at 9.95 set M & L. run road traverse on west ½ NE¼ & NE¼ 20. road no longer a road

---

7-1910 Ch Larson P130 B S28 N Front

- over

found stake & lime filled hole. set stone on top
16 x 20 x 20
- meas south 40.22 to corner set from W Fraser notes

8-1922 J Kerr B 1920 #22 P 18
run line between sections 20-21 5 26 21.7. corrected line
run west to center S. 20 a stone set pickle bar beside stone
at 2631.3 - no mention of what found at SE cor 20.
or what if anything set for quarter elsc.

12-1-69 J Kerr found stone on previous visual exploration
stone large limestone 23 x 20 x 8 very heavy. also found
1½" hole underneath filled with white lime as recorded
drove ¾ x 12" rod in lime hole set stone south of C/M and smaller
stone on east side slightly above C/M which is flush.
corner comes just southeast of large white oak corner post
of fence N-S-E. Northeast of corner stands a 26" hard maple
with natural raised scar on northwest side 6"x 12" center of scar
is 16 from C/M. (See Kerr Bk. -9 P. 18)

(7)

Sec. cor. 20-21-28-29 New Haven Twp.
#852105

Gov. Notes- John Cushing, Aug. 10, 1854, Dept. Sur.

80.00 Set corner post to sec. 20-21-28-29 from which:
Bur. Oak 10 in. N71W 18 lks.
Aspen 12 in. S31E 43 lks.
Bur. Oak 6 in. N85E 17 lks.

May, 1863 PC Compton Pg 70 No. 49 shows section Corner
(See survey No. Interior of sec 28