#852604

1 10-12-71 set C/M over 36" iron 2 Cords and orig stone & junk (1)

1/4 Corner 26-35 New Haven 108-15

2-1882 Hunter P 373 No 364 S 35 C, Gates, J. Bryant

Corner gone, no knowledge but much dispute and controversy as to where it should lie.

at temp stake M & L 40.02 1/2. (2641.65'

-16 south found small D. oak tree within inches of M & L.

19.96 (1317.36' - found stone 32 lks south (21.12'

placed by some error as corner.

-16 center NW 1/4 35' set marked stake M & L 20.15 (1329.9'

on E-W 1/16 line. 2 B Trees - 6" D oak S 35° W 44 lks

6" " N 40° W 14 "

11-1887 Hunter P 424 No 413 S 26 J Revelle, M Patterson.

Corner P 373 missing. replaced corner by mean - ores.

from east 40.02½. (2641.65. and from ⅛ south as
in P 373 set quarry stone 2x6x20
Corner came 1' north and -36 lks (23.76 west of fence east.
corner post.
- east set stone on line and ¼ of 40.02½. (660.41
- north set stake 9.98¼ then 9.98¼ then. 19.96½ to Center 26.

1-1902 2r Fraser P 28B. E½ 34, W½ 35 E W Daly.
found stone 37 lks west of post on east side of road.
- south set stake at 337½ (222.75 then (819.2 (540.54
(iron stake)
then. 8.35½ (551.43 (tree) 1314.72 total.
- west Witching stake corners 3.37½ & 8.19. set 8.25 (544.5 west of road.

10-22-68 Starr run aerial line south section 26, ¼ line.
- set ⅜ "x14" on hill brake 600'± west of N-S road. on ¼ line.
- this rod. lies 7.6' north of nails scar in base of 16" walnut.
- also set ½ "x18" rod on east edge traveled road. on true sec line.
- this rod random line -.55' S of true line
no
Corner ⅓ way from south gate
Card #2 - over

#852604 (2)

Card #2. 1/4 26-35 New Haven 10 8-15.
Kerr B 101 P20
random rod To help find or set this corner. Iron east
edge traveled road. in field drive 1/3 way from South gatepost -
- 21.25 To hard nail in RR tie gate post. NE
- 31.5 To Center walnut trd SE
- Corner must come close to this line, could be
anywhere E & W. - Aerial not a direct line - SE 26.00
SW 26 line fell 1.1 south of corner. so rod at 1/4 26-35
would be .55' south of trad line

10-12-71. found rod on E edge road - rod on hill west and
rod in center road set by Pete Higham on section line and
maybe midway (over)

10-12-71 dug with tractor, found recorded size limestone
3.11' south of corrected E-W line run by J Kerr 10-1968
- did not correct rod on hill west, set stone N side rod
so point could be found easily, walnut still in place.
- Perk Higham rod came 2.99 N and .41 E of stone found.
section corner 26-27-34-35 now in question. book 6.22 S.
Set old radio, junk & 36" V shaped 2" steel bar on E
side of stone centering over stone with C/M over all
35.57 SE to 40 D in center of 18" walnut up 30" SW side.
30.9 NE to small hard rail on NW corner RR tie post.
35.55 NEly to ○ in N end 15" galv field drive culv.
32.3 SEly " " "S" "
660 ± East to 3/8" x 4.3' reinf rod set on exact section
line by stones found and stub of old corner post.

New Haven 1/4 corner 26-35 #852604 3
Gen'l Land Office Courtney 1854
40.00 Set temp 1/4 Stone post
West on true line between Sect 26 & 35 N 9° 11' E
40.00 Set 1/4 Stone post from which a
Aspen 12 in S 81 W 50 l
White Oak 16 in S 78 E 100 l

Jan, 1862 Samuel McDowell Pg. 67 No. 94 used 1/4 Cor. to set Center Sec. 35 & break down West 1/2 sec. 35