/ 6-3-80 CIM #853004 ①

¼ corner 30-31 New Haven 108-15.
11-1874 Hunter P264 No 262 & 30 R Cornforth & others.
found stone in center road which M.V Roberts avers
was set by Robt Perry at site of original stake.
- 16 east set boulder 5 x 8 x 14. N & L 19.97½ (1318.35'
- east set stone at 6.3 chs (415.8' for line north
then 13.67½ (902.66' to 16 corner above.

---

govt meas west to east.

18.19	20.00	20.00	20.00
1200.54	1320.00	1320.00	1320.00

- Hunter east 2636.7.
- Larson west 2520.54 on ¼ line south [no point on E and line.

10-18-71 meas from. C/M set over orig stone, to west
- found 1/16 fence north. at 1320.4. R 1318.35 also.
properly fence north at 2224.0 ± R. 2228.9.
- found properly fence north at 2510 ±.
- found. property 1/4 line fence south at 2642. R 26367
10-20-71 dug 10.5' deep to bottom old road fill still much
black dirt but found nothing probed below oldest road
fill rest to hard and no reason to believe it in those stratas
- found 4x5x12 L stone at center section 30. in corner woods
also 1/16 stone east of center 30
- Corner could be replaced only by 1. finding 1/16 E where road
dug & probed to over 9' deep. 2. project & meas line from north
over center 30 stone and property corner at 1/4 19-30. (stakes 1875
with 2B trees. otherwise corner lost.

New Horse ¼ corner 30-31 #853004 (2
Gov't Meters Course 1854
4000 set temp ¼ set post
course N 89° 53' E on true line between
38.19 set ¼ set post in mound set 30-31
with trench & trees blazed sides

5-30-1980 (1980 Remon BK, Page 46) at T. Hunter property
corner 6.3 chs. East of ¼ Cr 30-31
Dug on line from Sec. Cr 29-30-31-32 over stone Fd.
at 1/16 West and from fence line North, West for x no. ft.
Dug 11' deep. No old wood left but found 9" diam.
handhead in black dirt. Could not tell if dug in or not
Boulder 3.8 W & 1.2 N of mail set on line from Sec. Cr
over 1/16 TN } 19.97 E Boulder } 23.78 E
} 16.96 N } 16.31 N

1/16 Cont of ¼ Cr 30-31 5-28-80 (1980 Remon BK. Page 47)
Dug and found stone boulder 5"x8"x14" set by Hunter
stone 7.5 deep. Set a 1"x36" iron rod over stone

Corner lies ± 4' South & E-W Road and ± 2' East of fence line North. Stone 2.35 East and .7 North of t.n.

RP. CSD in p.p. SW 106.16

Spike in top fe. cn. post North 36.02

6-3-1980 (1980 Remon. BK, Page 53) 1/4 Cor 30-31: Set a 20" CIM over a 3/4" x 21" thinwall pipe on line and at double the measure from Sec. Cor 29-30-31-32 over the 1/16th West (found) 5-28-80. This corner 7' East of fence South and 9' South of center of E-W road.

RP's:

— 1/2" pipe under fence South SSW 52.75

— Punched cross in top West end C.M.P. in field drive North NE 102.47

¼ Cr 30-31 New-Haven 108-15 #853004 (3)

5-27-80 Dug with the backhoe 9' deep from 4' South & 7' North of traverse nail & from 3' West to 4' East of the traverse nail. Found nothing.

5-28-80 After finding the 1/16 Cor, dug again to cover meas. & line from East & 6' East of the trav. nail Found nothing.