/ ~~4-12-71. found boulder - grand fogon around stone~~

5-15-1979 Set CIM #853104 (1)

1/4 corner south 1/4 31 New Haven 108-15
North 1/4 6 Kalmar 107-15.

2- 1870 Robt Perry. P 98 no 140 S6 C Kutzler.

. found post and stone ~~as corner~~. and proved it correct.

Run north line sec. 6 east to west. 79.22. (5228.5'
govt record 79.50 (5247.0'
came within 2/3 link

~~set~~ 1/4 corner at 40 chains from east ~~chor~~

19.86 (1310.8') To set oak post-chor 19.36 to boulder (1277.8

~~Noted the corner set by law which could be questioned.~~ ?

4-12-1971. Co surv. ~~found C I M~~ at twsp corner likely set by Perk Higbum. believed correct until proven otherwise - meas east on 10' ⑤ north. found recorded stone just S E

No Good!

(over)

¼ corner post at 2573.0 R 39.22. 2588.52
Cont meas east to N ¼ 5 or S ¼ 32 stone. 5313.2
could find nothing at S 31-32 on several attempts in
extensive digging operations. Decided best to set corner
at S 31-32 midway 2656.2 and on projected line from
Twsp corner over S ¼ 31. - 10' offset ame 11.15 North of S ¼ 31
and 13.1' north of S ¼ 32. - direct line would place S 31-32 at
12.07 south from 10' @ random. while direct from twsp corner
over ¼ corner would be 12.3 south - set at about 12.2 south.
- Note Perrup meas? seems to run erratic, long on W ½.
short on E ½ (2573.0 R 2588.52. - 2656.6 R 2640.0
- 16 fence east of stone found at N ¼ 6 . 1327.5 proving that
meas above fairly proportional. 1328.1 E ½.

#853104 (2)

¼ Corner South ¼ 31 New Haven 108-15
4-10-79 North ¼ 6 Kalmar 107-15
1/16th West (1979 Renomumentation Book Page 17)

We dug at Perrin's 1970 measure from the SW Cor 31 (found 1978) and found a 9"x9" square mark in clean clay 11.2 West and 1.0 South of the Traverse nail set on the south side of the C.P. to fence E-W-N. We retained the location of the mark by driving a ½" x 20" iron in the center of it (down 1½')

4-10-79
S¼ 31 We projected the line from SW 31 over the mark found at the 1/16th and again took Perrin's measure. This point came 6.19 East of the traverse nail set 1' East of the C.P. We dug from 4½ to 9½' East by 3½' N-S by 2½' Deep

but did not find anything. Mr. Mensing who owns SE¼ SW¼ and SW¼ SE¼ Sec 31 and the NW¼ NE¼ Sec 6 and whose family has owned there ¼ ¼'s since 1919 said he had no knowledge of this corner but that he had seen the stone at S. 31-32 when the road was graded when he was a boy 50 yrs ago

5-15-1979 Set a CIM over a ½" x 2' iron on the corner on line from the SW Cor 31 over the mark found at the 1/16th East on 4-10-79. and at Robert Perry's prorated measure (prorated against the meas. from the SW Cor 31 to the mark found at the 1/16th East) The corner is 7' East of the fence North and South and in line with the fence East and West

RP's: CSD in c.p. NW 25.42 CSD in N side c.p NW 7.03
CSD in fence post NE 23.92 CIM 1' deep.

1/4 corner South 1/4 31 New Haven 108-15 (3)
853104
North 1/4 C Kalmar 107-15

Got N.to

40.00 Set post & depressed bronze cap in small stone for quarter section corner. Built mound with trench. Planted S.E. Osage Orange, & N.E. Apple seeds.

1/4 Corner South 1/4 31 New Haven 108-15
North 1/4 C Kalamo 107-15

(4)

#853104

Gen'l Notes.

40.00 Set quarter section post

BK Oak 10 D 84½ E 10⅛

BK O. K14 D ~~58~~ W 68⅝