X 11-13-1975 - Set CIM. over ½"x18" rod #853304 (1)

¼ Corner south ¼ 33 New Haven 108-15
North ¼ 4 Kalmar 107-15

12-1897. H Fraser P614 No 558 S 33 J Altman A Hurd D Pierce.
found corner placed in 8-1893 in survey made then when stone 2x4x17 was placed in place. Pved stake found from. NEBT and stump SW BT.
-16 North. set stake N&L 20.00

H 1905 Robt Fraser P78B. SW ¼ 33. H Lake. D Altman S Searles.
found stake with stake beside it at corner of fence post.

-over-

-West drone oak stakes at 746 55/64 (492.9' then 12.44 49/64
(821.54' then 9.95 13/16 (657.2 then 9.95 13/16 (657.2 to SW 33

12-1916 Dwilliamsby Star P264B SE 1/4 S33 J Fraser & attorneys
found and used stone and stake.
- Meas east to SE cor 33 set M&L 2616.5
-16 North set stake M&L 1321.7 to stone center 33

1935 Co Hwy Dept B 78 - iron pipe & stone at fence cor.

1931 Book 6 #2 similar info as P264B.
Meas north to center 33-2643.5

11-13-75 New fences in area of corner. Probable clearing of trees. Dug in fence line from corner post N for 20'. Found nothing. Dug large area east and north of corner post

¼ Corner South ¼ 33 New Haven 108-15 (2)
North ¼ 4 Kalmar 107-15
#853304

as computed location but found nothing. Set CIM over ½" x 18" rod (deep) as corner. Set corner at double the line and measure from N¼ Sec 3 over J. Kerr's 1931 location of N Sec. Cor 3-4 (This corner was set M&L by J.K. in 1931 - True corner and Kerr's corner later found and referenced) as per his 1931 Survey. Corner is 3' E of fence N, 9' N of fence W, 244' S. of corner post to fences E and S in Section 33.

R.P.'s: CSD E side corner post SSW 9.19
Spike in E side 30" Elm N 240.52

Mean W = 2628.581 Mean E = 2601.51

(1/16 W) ~~10 28 15~~ Dug N and W of corner post but found nothing! Exact M & L came 1' ± N of corner post after setting 1/4 Cor 4-9

Nov, 1856 Thos. Hunter Pg. 18 No. 30 shows 1/4 Post. 1/16 North 20.03 chs. M&L - B.T.'s (N13°E 38 lks.) (S80°E 18 lks.)

Aug. 1893 William Fraser Pg. 18 No. 38 An Addition to Thos Hunters Survey - Found stake as 1/4 Corner from witness Tree Planted stone (2 x 4 x 17)

Feb., 1863 P.C. Compton Pg. 68 No. 95 shows 1/4 Stake used for breakdown of S.W. 1/4 Sec. 33

Feb, 1867 H.E. Horton Pg. 81 No. 122 Shows 1/4 Corner 1/16 west 19.96 chs, 1/16 South 19.80 chs. 1/16 west B.T.'s (S40°W 28 lks) (N56°E 20 lks)

1/4 corner North 1/4 33 New Haven 10S-1E (3)
North 1/4 4 Kalmia 10S-1E
#853304

Corner Notes
40.00 Set quartz stone pond level
Black Walnut 15 S 50° W, 5
Elm 5 N 72° E 3