OLMSTED COUNTY, MINNESOTA.

HALF SECTION MAP

SECTIONS 28 & 29 TOWNSHIP 107 , N. R. 13 W.

SCALE 1 INCH = 400 FEET.

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Registered Land Surveyor under the laws of the State of Minnesota.

Roger W. Brand

Date Dec. 4, 1972 Reg. No. 8952

Lines previously run ——— ———

Corners located or set ◎

Corners formerly set & used ●

N

Nail in boulder Tree Temp Corner – Location Acceptable

Cast iron monu. in place and Acceptable

Cast iron monu. in place and Acceptable

Nov. 1972 Found 1/4 Cor. Limestone by Hunter

Temp. iron rod Set as Witness Acceptable Location

Cast iron monu. set by Kerr Acceptable Corner

ch. 1316.9

ch. 1316.9

ch. 2616.3

2625.48 2624.82 T. Hunter e/ec.

1312.41

1312.41

Set 1/2" pipe

1 1/2" pipe in pl.

Iron rod in pl. 4' W. of fe

29

28

Set by Cast iron monu. – set and prorated N-S Measure

1" iron pipe in place Acceptable Corner

1" iron rod Set by McGhie & Betts 13' W. of fence

13'

Appx. fence Location

Sec.

Sec.

--2613.6 ± by Computation--

Steel fe post Set by Kerr as 1/4 Cor. Post now removed & wood Stake reset Post was 29.0 East & 9.37 South of our 1/4 Corner

5.9'

Cast iron monu. Set by Kerr did not check E-W 1/4 line

Oct. 1972 Found – Boulder Set Cast iron Monu. over Stone

2620.2 T. Hunter e/ec.

2619.55' e/ec.

2628.50 e/ec.

1" 1/2 rod in place 15' W. & 7.5' So. of Cor. fe post

Iron shaft in place Acceptable Corner

Reset 5/8 iron rod – 1/4 Cor Set on line between Sec. Corners and by using lines of Occupation at points 1/4 mi., 3/4 mi., and N. 1/4 Cor.

1/2" rod in place

16.66'

0.7'

1 1/2" pipe by McGhie & Betts

18.8'

Oct. 1972 fd. Limestone Set Cast iron monu. over Stone

2645.66 e/ec.

Set iron rod

1322.83

1322.83

89°38'

Oct. 1972 fd. Wood Stake & Limestone Set Cast iron monu. over Stake

1323.68

2647.35 e/ec.

Set iron rod

1323.67

Oct. 1972 fd. Boulder Stone Set Cast iron monu. over Stone

Drwg No. 3-41

3-41A