OLMSTED COUNTY, MINNESOTA.
SECTION MAP

SECTIONS 28 & 29 TOWNSHIP 107 , N. R. 13 W.

SCALE 1 INCH 400 FEET.

N

Roger W. Brand
Dec. 4, 1972

Lines previously run ——— ———
Corners located or set ◎
Corners formerly Set & used ⊙

9999/596
2731/2950

nail in boulder Tree
Temp Corner—Location Acceptable
Reset C.I.C/P2 on 3-22-77
.64 west
.21 South of 120d

120d spike

Cast iron monu. inplace and Acceptable

Cast iron monu. inplace and Acceptable

Nov. 1972 Found 1/16 cor. Limestone by Hunter

Temp. iron rod Set as 1/4 cor. Acceptable Location

Cast iron monu. Set by Kerr Acceptable Corner

N89°59'44"E 2623.61

(448.59) 1977

2634.57 (1977)

accumed E-W 2649.50

2203.64 S 15° 56' 56.98" W 2203.44 (1977)

2634.57 (1977)

90°22'33"

Ch. 1316.9

Ch. 1316.9

N 0°11'46"W 2678.78

Ch. 2616.3

Sec. 29 47

N 15°29' 55"E 2581.97

S 5°40' 15" E 2667.12

N 7°22' 21" E

N 89°18' 10" E 660.55 rec.

N 89°58' 55" E 66.63

N 89°53' 16" E 2640.22

ch. 57.0 iron rod Set by McGhie & Betts 13' W. of fence

S 0°02' 37" E 1269.34

Apprx. Center of Creek

Trans. wall

7326.331 5330.318

5291.318 S 89° 52' 57" W

Comp. Cen. Set 3/4" rod

13'

120' 37' 18"

Set by Cast iron monu. - Set and prorated N-S measure

7375.445 8032.483

2613.6 ± by Computation

steel fe post Set by Kerr as 1/4 Cor. Post now removed & wood stake reset Post was 29.0 East & 9.37 South of Our 1/4 Corner

N 89° 52' 56" E 2613.6 ± Meas.

Cast iron monu. Set by Kerr did not check E-W 1/4 line

5.9'

Sec. 29

Sec. 28

6130.590 2745.188

809.45

6654.176 3855.521

6025.391 2746.072

6657.812 thru R NO 3375.952 S Good

Correct 1/16 Should be 12 E. & 3' N.

1/2" rod inplace 15' W. & 7.5' So. of Cor. fe post

2620.2 T. Hunter 2619.55 elec.

2619.944 Inv.

2628.50 elec.

Oct. 1972 Found - Boulder Set Cast iron monu. over Stone

6-11-76 - set c.i.m. Iron Shaft inplace Acceptable Corner

S 86° 41' 26" W 4589.09

Reset 5/8 iron rod - 1/4 cor Set on line between Sec. Corners and by using lines of Occupation at points 1/4 mi., 3/4 mi., and N. 1/4 Cor.

4731.693 5236.707

Use on Line Pt. 4749.76 5395.94

Nail

N 69° 33' 08" W 724.94

1008.528 734.472

Oct. 1972 fd. Limestone Set Cast iron monu. over Stone

0.7'

Oct. 1972 fd. Wood Stake & Limestone Set Cast iron monu. over Stake

89° 38'

2642.414 S 89° 52' 25" W

1/2" rod inplace

16.62

2618.298 S 89° 52' 21" W

1/2" pipe by McGhie & Betts

12.8

2645.66 elec.

Set iron rod

1322.83

1322.83

2647.35 elec.

Set iron rod

1323.68

1323.67

Oct. 1972 fd. Boulder Stone Set Cast iron monu. over Stone

5260.713 S 89° 52' 23" W

1308.2

Addn Work in Sec. 29 — June 1976

Drwg. No. 3-41

3-41B